

Pipeline Pigging Products

INCORPORATED



PIPELINE PIGGING PRODUCTS

INDUSTRY EXPERIENCE, RESEARCH, KNOW HOW



Pipeline Pigging Products is a manufacturer of internal pipeline cleaners referred to in the trade as “Poly Pigs.”

Constructed of flexible open cell polyurethane foam and various external wrappings, Poly Pigs have the ability to negotiate short radius bends, ells, tees, multi-dimensional piping and reduced port valves.


The slightly oversized Poly Pig forms a “sliding seal” in the pipe, and is designed to remove product buildup, foreign matter and loose sediment.

A few of the benefits that Poly Pigs can offer are:

- Increased pipeline carrying capacity
- Improved product quality
- Power savings by reducing pump pressure
- Confirmation of pipe and flow integrity

Pipeline Pigging Products offers Poly Pigs in a wide variety of styles (drying, wiping and scraping) to accommodate almost any application, such as oil & gas transmission, municipal, petro chemical, pulp and paper and process piping systems.

With over 30 years of manufacturing, experience, research, and application, our knowledge of Poly Pigs is unsurpassed in the industry.









Poly Pigs run the pipeline, pushing debris, corrosion and mineral build up ahead of them until the lines are clean and operating at a much higher capacity.

INDUSTRIAL SERIES






APPEARANCE	STYLE	TYPE	DENSITY	APPLICATIONS
	G1	Swab	<u>1-2 lbs. cubic foot</u> (16 - 32 Kg/M3)	Light Duty Drying
	G2*	Coated Swab	<u>1-2 lbs. cubic foot</u> (16 - 32 Kg/M3)	Light Duty Wiping
	G6*	Carbide (Grain)	<u>1-2 lbs. cubic foot</u> (16 - 32 Kg/M3)	Light Duty Scraping
	RX3	Bare	<u>5-7 lbs. cubic foot</u> (80 - 112 Kg/M3)	Regular Duty Drying
	RX4*	Coated	<u>5-7 lbs. cubic foot</u> (80 - 112 Kg/M3)	Regular Duty Wiping
	RX5*	Wire	<u>5-7 lbs. cubic foot</u> (80 - 112 Kg/M3)	Regular Duty Scraping
	RX6*	Carbide (Grain)	<u>5-7 lbs. cubic foot</u> (80 - 112 Kg/M3)	Regular Duty Scraping
	C3	Bare	<u>8-10 lbs. cubic foot</u> (128 - 160 Kg/M3)	Heavy Duty Drying
	C4*	Coated	<u>8-10 lbs. cubic foot</u> (128 - 160 Kg/M3)	Heavy Duty Wiping
	C5*	Wire	<u>8-10 lbs. cubic foot</u> (128 - 160 Kg/M3)	Heavy Duty Scraping
	C6*	Carbide (Strap)	<u>8-10 lbs. cubic foot</u> (128 - 160 Kg/M3)	Heavy Duty Scraping

*Available with Rotating Pattern (see back page)

SPECIAL APPLICATION SERIES

APPEARANCE	STYLE	TYPE	DENSITY	APPLICATIONS
	PB	Power Brush	<u>8-10 lbs. cubic foot</u> (128 - 160 Kg/M ³)	Maximum Scraping
	CPB	Coated	<u>8-10 lbs. cubic foot</u> (128 - 160 Kg/M ³)	Non-abrasive scraping
	RXSS	Single Spiral	<u>5-7 lbs. cubic foot</u> (80 - 112 Kg/M ³)	Regular wiping
	FD-5	Foam Disc	<u>5-7 lbs. cubic foot</u> (80-112 Kg/M ³)	Regular duty Liquid Removal; bi-directional runs
	FD-8	Foam Disc	<u>8-10 lbs. cubic foot</u> (128-160 Kg/M ³)	Heavy duty Liquid Removal; bi-directional runs
	Stud Pig		<u>8-10 lbs. cubic foot</u> (128-160 Kg/M ³)	Extra hard scale removal

OPTIONS

	Rotating Pattern	Promotes longer even wear in most applications Available on all coated and wire styles
	Rope Loop(s) Cable Loop(s)	For handling; pulling Available on all styles
	Double Dish	Liquid removal; bi-directional runs Available on all styles
	Double Nose	Bi-directional runs with pipe reductions Available on all styles
	Cavity	For housing electronic tracking transmitter Available on all styles

Pipeline Pigging Products Incorporated

P.O. Box 692005
Houston, Texas 77269
1 (800) 242-7997
P: (281) 351-6688
F: (281) 255-2385
www.pipereg.com

Our area representative is: